<u>4766-2-08</u> <u>Vehicle inspections.</u>

- (A) The board shall inspect all ambulance(s) and non-transport vehicle(s) for roadworthiness and for appropriate equipment as prescribed in rule 4766-2-10 of the Administrative Code.
- (B) Before ambulance or non-transport vehicle receives permit, it must comply with the following requirements:
 - (1) Roadworthiness requirements:
 - (a) High and low beam headlights shall be operational;
 - (b) Clearance lights, marker lights and reflectors shall be operational (if applicable);
 - (c) High beam indicator light (on dashboard) shall be operational;
 - (d) Left and right tail lights shall be operational;
 - (e) Left and right front turn signals shall be operational;
 - (f) Left and right rear turn signals shall be operational;
 - (g) Left and right brake lights shall be operational;
 - (h) License plate light shall be operational;
 - (i) Back up light(s) shall be operational;
 - (j) Audible back up alarms shall be operational;
 - (k) Tread depth on each tire shall be minimum of 1/16 inch;
 - (1) Tread or sidewall of tires shall be free of major deformities;
 - (m) Rims/wheels shall be free of significant damage;
 - (n) Brake pedal travel shall not exceed:
 - (i) Two thirds travel in vehicles with non-assisted brakes;
 - (ii) Four fifths travel in vehicles with power assisted brakes;
 - (o) Emergency/parking brake shall be operational;
 - (p) Windshield without breach, unobstructed;
 - (q) Exhaust system without breach;

<u>4766-2-08</u>

- (r) Windshield wipers and washer shall be operational;
- (s) Steering shaft secure with no more than one quarter turn play;
- (t) Rear view mirrors without breach;
- (u) Horn shall be operable and audible;
- (v) Safety belts for driver and passengers shall be operational and free of visible damage;
- (w) Vehicle body and frame structural integrity without breach;
- (x) License plates on front and rear of vehicle (if required by state law);
- (y) Emergency lighting shall be operational;
- (z) Siren shall be operable and audible.
- (2) A MTO must demonstrate proof that the ambulance(s) complies with all specifications set forth in the general service administration star-of-life ambulance, KKK-A-1822 standard in effect at the date of manufacture of the ambulance(s) chassis by one of the following:
 - (a) KKK-A-1822 placard/sticker;
 - (b) Certificate issued by the manufacturer;
 - (c) Signed affidavit by the manufacturer certifying KKK-A-1822 compliance.
- (3) The name of the MTO shall be permanently affixed with each letter being a minimum of three inches in height on both sides and each letter being a minimum of one and one half inches in height on the rear of the ambulance.
 - (a) If a MTO is under contract which requires other signage, the MTO's name and service code shall be permanently affixed with each letter being at a minimum of three inches in height on both sides and one and one half inches in height on the rear of vehicle.
- (4) All board identified deficiencies must be corrected. The vehicle shall be placed out-of-service until it passes reinspection by the board.
- (C) Vehicles not titled as ambulances are not eligible for permits as ambulances, but may be issued permits as "non-transport vehicles" pursuant to section 4766.07 of the Revised Code, provided they fall within the definition of such vehicles in division (Q) of section 4766.01 of the Revised Code.

<u>4766-2-08</u>

(D) Upon issuance of a vehicle permit, each licensed MTO shall apply the decal on the outside of the right rear window in accordance with division (B)(2) of section 4766.07 of the Revised Code on each ambulance and non-transport vehicle.

- (1) The permit must be unobstructed at all times.
- (E) A permit is not transferable.
- (F) The board may conduct routine unannounced inspections at any location of licensed MTO at any time, including night or weekend inspections to determine compliance with Chapter 4766. of the Revised Code and Administrative Code to include, but not limited to, ambulance(s) and non-transport vehicle(s).
- (G) A permitted ambulance or non-transport vehicle shall maintain compliance with roadworthy requirements set forth in this rule at any time it is used as an ambulance or non-transport vehicle.
- (H) Each permitted vehicle shall be free from dirt, stains, impurities and/or foreign matter in driver's compartment and ambulance patient care compartments.

4766-2-08 4

Effective: 07/02/2009

R.C. 119.032 review dates: 07/02/2014

CERTIFIED ELECTRONICALLY

Certification

06/22/2009

Date

Promulgated Under: Statutory Authority: Rule Amplifies: 119.03 4766.03

4766.04, 4766.07