

901:10-2-03

Geological explorations.

(A) ~~Fabricated structures - A subsurface geological exploration shall be conducted prior to installing a fabricated structure. A subsurface geological exploration for a liquid manure fabricated structure shall be conducted under the supervision of an engineering geologist or a professional engineer. A subsurface geological exploration shall be completed for fabricated structures as described below~~determine the following:

(1) For fabricated structures storing solid manure.

(a) Evaluate the suitability of the soil to provide the appropriate load bearing strength for the proposed fabricated structure by use of a soil survey or by a geological exploration conducted in accordance with this rule. The director may require on-site subsurface geological explorations depending on the soil survey, depth of the structure to be installed below existing grade and type of structural loading of the fabricated structure.

(2) For fabricated structures storing liquid manure.

The subsurface geological exploration and report shall be completed under the supervision of an engineering geologist or a professional engineer, and shall be in compliance with, and describe, the following:

(a) The subsurface geological exploration shall include a minimum of three test pits or borings. The ~~Place a minimum of two~~ test pits or borings must be at regular intervals and within a reasonable distance of the boundaries of the proposed fabricated structure. Additional, unless more ~~test pits or borings may be~~ required by the director or the professional engineer or engineering geologist. The test pits or borings shall extend a minimum of five feet below the planned bottom of the fabricated structure.

(b) The test pits or borings shall extend a minimum of five feet below the planned bottom of the fabricated structure. In addition, a representative number of test pits or borings shall extend deep enough to determine if the fabricated structure meets the siting criteria from the uppermost aquifer described in rule 901:10-2-02 of the Administrative Code. Upon completion, any boring or pit used for sampling shall be properly plugged and sealed.

(c) The classification of the soil material shall be provided, as set forth in the appendix to this rule.

(d) The in-situ hydraulic conductivity of the soil material shall be determined, based on lab results, within five feet below the planned bottom of the fabricated structure.

~~(b)(e)~~ Evaluate The subsurface geological exploration shall evaluate the suitability of the soil to provide the appropriate load bearing strength for the proposed fabricated structure as set forth in the appendix to rule 901:10-2-05 of the Administrative Code.

~~(e)(f)~~ Determine The subsurface geological exploration shall determine soil strength values so that lateral earth pressures can be calculated as set forth in the appendix to rule 901:10-2-05 of the Administrative Code.

~~(d)(g)~~ Whether The subsurface geological exploration shall evaluate whether the proposed fabricated structure is to be located within a karst area; and

~~(e)(h)~~ Ground water quality characteristics. Ground water shall be sampled from a well existing at the facility or, if no well exists at the facility, from a well that is constructed in accordance with rule 3701-28-12 of the Administrative Code. A well installed or otherwise approved for use to satisfy the requirements of this rule, shall also be used to satisfy the annual ground water sampling and analysis required by rule 901:10-2-08 of the Administrative Code.

~~(f)(i)~~ In the event that the director determines that ground water monitoring shall be required to satisfy the requirements of this rule or rule 901:10-2-02 of the Administrative Code, then a ground water monitoring program shall be designed, installed, and implemented as approved by the director in a permit to install and permit to operate.

(B) Manure Storage Ponds or Manure Treatment Lagoons - A subsurface geological exploration shall be completed for manure storage ponds or manure treatment lagoons as described below.

The subsurface geological exploration and report shall be completed under the supervision of an engineering geologist or a professional engineer, and shall be in compliance with, and describe, the following:

(1) The subsurface geological exploration shall include a minimum of four test pits or borings. The test pits or borings must be at regular intervals and within a reasonable distance of the boundaries of the proposed manure storage pond or manure treatment lagoon. Additional test pits or borings may be required by

the director or the professional engineer or engineering geologist.

- (2) The test pits or borings shall extend a minimum of five feet below the planned bottom of the manure storage pond or manure treatment lagoon. In addition, a representative number of test pits or borings shall extend deep enough to determine if the manure storage pond or manure treatment lagoon meets the siting criteria from the uppermost aquifer described in rule 901:10-2-02 of the Administrative Code. Upon completion, any boring or pit used for sampling shall be properly plugged and sealed. Any pit used for sampling that is within the construction boundaries of the concentrated animal feeding facility, the manure storage pond or the manure treatment lagoon shall be restored by the addition of cohesive soil compacted in lifts no greater than six inches;
- (3) The classification of the soil material shall be provided, as set forth in the appendix to this rule;
- (4) The in-situ hydraulic conductivity of the soil material shall be determined, based on lab results, within five feet below the planned bottom of the manure storage pond or manure treatment lagoon;
- (5) The subsurface geological exploration shall evaluate the suitability of the soil material to provide adequate sealing of the bottom of the manure storage pond or manure treatment lagoon and construction of the planned embankments as described in rule 901:10-2-06 of the Administrative Code;
- (6) The subsurface geological exploration shall evaluate whether the proposed manure storage pond or manure treatment lagoon is to be located within a karst area;
- (7) Ground water quality characteristics. Ground water shall be sampled from a well existing at the facility or, if no well exists at the facility, from a well that is constructed in accordance with rule 3701-28-12 of the Administrative Code. A well installed or otherwise approved for use to satisfy the requirements of this rule, shall also be used to satisfy the annual ground water sampling and analysis required by rule 901:10-2-08 of the Administrative Code.
- (8) In the event that the director determines that ground water monitoring shall be required to satisfy the requirements of this rule or rule 901:10-2-02 of the Administrative Code, then a ground water monitoring program shall be designed, installed, and implemented as approved by the director in a permit to install and permit to operate.
- (9) Based on the results of the subsurface geological exploration and determinations by the engineering geologist, professional engineer or the director, additional tests may be required to determine the potential need for a liner and the liner specifications;

(10) The department may require additional subsurface geological explorations depending on the soils and geological formations on site to ensure the protection of the ground water, surface water or the structural integrity of the manure storage pond or manure treatment lagoon. The subsurface geological exploration shall refer to the Ohio department of natural resources, division of soil and water resources, ground water pollution potential (DRASTIC) maps to determine the pollution potential for each site, the pathways of contamination, if any, and whether additional design is needed to protect water and ground water.

~~(B) Prior to installing a manure storage pond or manure treatment lagoon, a subsurface geological exploration shall be conducted under the supervision of an engineering geologist or a professional engineer for the storage pond or treatment lagoon.~~

~~(1) A subsurface geological exploration shall be conducted on each new or expanding manure storage pond or manure treatment lagoon.~~

~~(2) The subsurface geological exploration shall be performed within a reasonable distance of the manure storage pond or manure treatment lagoon boundaries; shall include a minimum of four test pits or borings placed at regular intervals and shall determine the following:~~

~~(a) The type and hydraulic conductivity of the soil material present from the ground surface to a depth of five feet below the planned bottom of the manure storage pond or manure treatment lagoon;~~

~~(b) Suitability of soil material to provide adequate sealing of the bottom of the manure storage pond or manure treatment lagoon and construction of planned embankments;~~

~~(c) Whether the proposed manure storage pond or manure treatment lagoon is to be located within a karst area;~~

~~(d) Ground water quality characteristics. Ground water shall be sampled from a well existing at the facility or, if no well exists at the facility, from a well that is constructed in accordance with rule 3701-28-12 of the Administrative Code. A well installed or otherwise approved for use to satisfy the requirements of this rule, shall also be used to satisfy the annual ground water sampling and analysis required by rule 901:10-2-08 of the Administrative Code.~~

~~(e) In the event that the director determines that ground water monitoring shall be required to satisfy the requirements of this rule or rule 901:10-2-02 of the Administrative Code, then a ground water monitoring program shall be designed, installed, and implemented as approved by the director in a permit to install.~~

- ~~(f) The exploration pits or borings shall extend a minimum of five feet below the planned bottom of the manure storage pond or manure treatment lagoon. Upon completion, any boring or pit used for sampling shall be properly plugged and sealed. Any pit used for sampling that is within the construction boundaries of the concentrated animal feeding facility, the manure storage pond or the manure treatment lagoon shall be restored by the addition of soil compacted in lifts no greater than six inches;~~
 - ~~(g) Based on the results of the subsurface geological exploration and determinations by the engineering geologist, professional engineer or the director, additional tests may be required to determine the potential need for a liner and, if necessary, the type of liner to be installed;~~
 - ~~(h) The department may require additional subsurface geological explorations depending on the soils and geological formations on site to ensure the protection of the ground water, surface water or the structural integrity of the manure storage pond or manure treatment lagoon. The subsurface geological exploration shall refer to the Ohio department of natural resources, division of water ground water pollution protection (DRASTIC) maps to determine the pollution potential for each site, the pathways of contamination, if any, and whether additional liners are needed to protect water and ground water.~~
- (C) The results of subsurface geological explorations performed in accordance with paragraphs (A) and (B) of this rule shall be included in a report prepared by an engineering geologist or a professional engineer and submitted with the facility design plans.
 - (1) The report shall include but not be limited to an analysis or evaluation that demonstrates that the information provided meets the requirements of rules 901:10-2-01 to 901:10-2-06 of the Administrative Code, and as follows for each applicable type of manure storage and treatment facility:
 - (a) For any planned manure storage or treatment facility, the analysis or evaluation shall provide the following information:
 - ~~(a)(i) Location~~ A plan and profile view of the of a facility wellwells, and any exploration pits and borings shown in relation to the manure storage or treatment facilityplus locations and depths of soil samples;
 - ~~(b)(ii) Available Ohio department of natural resources, division of soil and water resources~~ division of water, water well logs of wells

located within a minimum of one thousand feet of the planned manure storage or treatment facility;

~~(e)(iii) Geologic information~~ Subsurface materials identified using either the group classification system by the American association of state highway and transportation officials or the unified soil classification system appended to this rule;

(iv) Identification of the uppermost aquifer at the site and the criteria used to make this determination.

(b) For any planned liquid manure fabricated structure, manure storage pond, or manure treatment lagoon, the analysis or evaluation shall also provide the following additional information:

~~(d)~~(i) Evidence of seepage or ground water conditions and depths in pits or borings;

~~(e)(ii)~~ Determination of the suitability of in-situ soils to provide an acceptable liner system for the planned facility, or lining recommendations when the in-situ soils are not suitable, which shall include remold permeability tests of planned liner material;

(iii) The results of the soil tests.

~~(f)(c)~~ For any planned manure storage pond or manure treatment lagoon, the analysis or evaluation shall also provide the following additional information: Recommendation from the laboratory analysis of the compactive effort or soil density, and soil moisture requirements needed during construction to achieve design hydraulic conductivity;

~~(g) The results of the soil tests; and~~

~~(h) An analysis or evaluation that demonstrates that the information provided meets the requirements of rules 901:10-2-01 to 901:10-2-06 of the Administrative Code, and as follows for applicable type of manure storage and treatment facility:~~

~~(i) For a solid manure fabricated structure, an analysis or evaluation shall provide the information required by paragraphs (C)(1)(a), (C)(1)(b), (C)(1)(e), and (C)(1)(h) of this rule.~~

~~(ii) For a liquid manure fabricated structure, an analysis or evaluation shall provide the information required by paragraphs (C)(1)(a), (C)(1)(b), (C)(1)(e), (C)(1)(d), (C)(1)(g) and (C)(1)(h) of this rule.~~

~~(iii) For a manure storage pond or manure treatment lagoon, an analysis or evaluation shall provide the information required by paragraphs (C)(1)(a) to (C)(1)(g) of this rule.~~

- (2) Based on the results of the tests of this rule the professional engineer, engineering geologist, or director may require additional explorations that may include laboratory testing of soils and additional ground water monitoring wells.

(D) Laboratory testing and analysis:

- (1) Soil samples taken during the subsurface geological exploration shall be tested in accordance with approved or certified soil testing procedures..
- (2) Tests and results reported shall include, but not be limited to, hydraulic conductivity, dry unit weight, Atterberg limits, and standard compaction with recompaction to achieve design hydraulic conductivity.
- (E) Upon request by the owner or operator and subsequent written approval from the department field changes may be made in order to meet site-specific conditions during construction. The owner or operator shall demonstrate that such changes shall be at least as protective of the ground water, surface water and the structural integrity of the manure storage or treatment facility as requirements of this chapter.

Effective: 09/01/2011

R.C. 119.032 review dates: 05/10/2011 and 07/18/2016

CERTIFIED ELECTRONICALLY

Certification

07/18/2011

Date

Promulgated Under: 119.03
Statutory Authority: 903.08, 903.10
Rule Amplifies: 903.01, 903.02, 903.04, 903.08, 903.082, 903.09,
903.10
Prior Effective Dates: 7/2/2002, 9/15/2005