

901:9-2-09

Ball and bag tossing games.

- (A) In any game at a fair in which balls or other objects are rolled or slid on a platform of any kind, the platform shall be level laterally, unwarped, and have no obstruction of any kind between the players and the targets. Balls must be round, solid and firm.
- (B) Basketball-type games. Games resembling basketball, but having rims or hoops with an inside diameter of less, or greater than, eighteen inches. The difference between the inside diameter of the rim and the outside diameter of the ball shall be no less than three and one-quarter inches. All rims shall be circular. Rim size shall be posted on the backboard and the game may not be called basketball. The ball's air pressure must be within the manufacturer's recommended air pressure. If the ball does not have an air pressure recommended by the manufacturer or the manufacturer's air pressure can not be located the ball's air pressure must be between 7.0 to 9.0 psi at the time of play.
- (C) Basketball games. The basket or hoop shall be ten feet high and have an inside diameter ~~of~~ of eighteen inches. A regulation-size basketball with a minimum circumference of twenty-nine and one-half inches and a maximum of thirty inches, with a weight minimum of twenty ounces and maximum of twenty-two ounces shall be used for play. The ball's air pressure must be within the manufacturer's recommended air pressure. If the ball does not have an air pressure recommended by the manufacturer or the manufacturer's air pressure can not be located the ball's air pressure must be between 7.0 to 9.0 psi at the time of play.
- (D) Football toss and similar games. Operators of this game, where a tire or hole is used as a target, shall provide regulation-size footballs or similar objects to be thrown, and the clearance in the target shall be at least one inch measured from the largest part of the football or other object on one side. No obstruction shall be permitted.
- (E) Pan ball or box ball game. This game shall be operated in a level position at all times. The use of rubber, plastic or cork balls is prohibited. However, a plastic ball with holes (wiffle ball) may be used to play this game. The table or stand supporting the pans or boxes shall not exceed three feet in height from the ground. If the game is trailer-mounted, the inspector shall determine the height of the base on which the game is set. The number of balls used to play this game shall not exceed four.
- (F) Ping pong ball fish bowl game. The fish bowls shall be not more than one inch apart in any direction. The measurement shall be that at the location of the widest portion of the bowl in relationship to all adjacent bowls. The table or stand supporting the fish bowls shall not exceed four feet in height from the ground. If the game is trailer-mounted, the inspector shall determine the height of the base on which the game is set. The width of the opening of the fish bowl shall be such that there will be not less than one inch from center position of the ball on one side.

- (G) Pop bottle ball game, bottle tip-em-over. Bottles shall be kept at least twelve inches from any obstruction so bottles are free to fall over at all times. Bottles shall be placed side by side in an upright position, bottom down, on the supporting platform and shall be parallel with the front of the game. The ball shall be tossed underhand. A leather-covered ball, approximately the same diameter as a baseball and weighing no less than one and one-half ounces, shall be used. One ball shall be used to play this game. Both bottles over wins. Boards shall not be waxed. Operators who desire to operate with four bottles and two balls may play in a similar fashion.
- (H) Roll-a-game. The board shall be rigidly mounted, level laterally and unwarped with no obstructions which could cause the ball to jump. All slots or holes shall be in an even row at the back of the board and shall not be staggered. The balls shall be solid and round at all times. The slope shall not exceed one inch per foot of board length. All openings or slots shall be of the same width.
- (I) Clown pop-em-in, stars, lion's mouth, and similar games. This game shall have at least one-half of an inch clearance on one side of the ball, and the target shall not be over six feet in distance from the front barrier. Motion of the game will be permitted if constant and not erratic. The approval by the director or his designee is required for a moving target.
- (J) Huckla buck kegs, milk can or similar game. These games shall be set on a frame and kept level at all times. The use of rubber and/or plastic balls is prohibited. The width of the opening of the kegs in huckla buck, milk can or similar games shall be such that there shall be no less than three-quarters of an inch clearance on one side. There shall be at least a four foot clearance from any obstructions above or around the cans.
- (K) Milk bottle ball game. No bottle shall weigh over three pounds. All bottles shall be free from defects and each set shall be uniform in size. The base on which the bottles sit shall be not less than eighteen inches from the ground. If the game is trailer-mounted, the inspector shall determine the height of the base on which the game is set. The front barrier shall not be higher than the base on which the bottles sit. The base shall be at least six feet from the front barrier. A rim not to exceed one-half of an inch will be permitted if operating the game "all over". No obstructions whatsoever will be permitted around the base on which the bottles sit if operating the game "all off". This game must be played with a rubber or leather covered softball with a minimum weight of five ounces.
- (L) Break the bottle, plate, and similar games. Targets shall be placed in a stationary rack at least twenty-four feet from the barrier with (no exceptions for trailer-mounted games). A protective covering shall be provided on three sides and the top for

public safety. A canvas drop shall be used. Balls must be inspected for embedded glass before being offered to the player. Plastic or bisque plates or discs shall have a minimum distance of six feet clearance from the front portion of the trailer. In the break the plate game, the distance between the plates must be less than the diameter of the ball thrown when the object of the game is to break two plates with one ball to win. All bottles need to uniform in shape and size. Only baseballs as described in paragraph (U)(1) shall be used.

- (M) Dunking machine or similar games. Persons seated on the target seat shall not use foul or offensive language and shall be properly dressed. The use of rubber, plastic, or cork balls is prohibited.
- (N) Cat rack. The rack may consist of one or more tiers. Shelves shall be level. Cats shall not weigh more than two pounds. Cats do not have to be knocked from the shelf to be considered over (same as if game is played when cats are hinged). Canvas backdrop shall not interfere with the falling cat nor shall there be any other obstruction to prevent the cat from falling. Front molding (rail) on the shelf shall not extend over one inch above the shelf and may be padded to lessen the chance of rebound balls. Balls must be the size of baseballs and weigh not less than three ounces.
- (O) Slat racks. Hinges on racks using fixed targets shall work freely to permit targets to fall over when hit.
- (P) Beverage can - bean bag can. This game shall be operated with either six or nine empty cans and may be played "all over" or "all off". The platform shall be no greater than twenty-one inches in diameter or a twenty-one inch square with the height being no less than thirty inches and no higher than fifty-two inches from the ground. If the game is trailer-mounted, the inspector shall determine the height of the base on which the game is set. Cans shall be placed no more than three-eighths of an inch apart. Two bean bags, three inches by three inches, with a minimum weight of two ounces shall be used. Cans shall have clearance of the can plus three inches. A lip not to exceed one-eighth of an inch will be permitted. Cans are to be stacked "4-3-2" or "3-2-1". No obstructions whatsoever shall be permitted around the base on which the cans sit if operating the game "all off".
- (Q) Bank-a-ball game. This game will be operated with the following requirements:
- (1) Must be played with standard unaltered wiffle ball (a hollow plastic ball with holes).
 - (2) Foul lines, edge lines and borders will not be permitted on bank board.

- (3) Baskets must be standard-size clothesbaskets and stationary to frame.
 - (4) Edge shots count.
 - (5) The angle of the bank board must be no less than sixty degrees off plumb, and no greater than seventy degrees off plumb, away from player. The operator must keep on location a tool to attest to and maintain this standard.
 - (6) The center of the basket must be positioned no further away from the player than the bottom edge of the bank board. It may be placed closer to the player.
 - (7) The bottom distance between the edge of the bank board and the top of the basket shall be no greater than twenty-four inches.
 - (8) The maximum distance that the player is required to stand away from the bottom of the board is six feet.
- (R) Slam dunk game (bank-a-ball type - Dobco manufacturing). This game will be operated with the following requirements:
- (1) Must be played with standard unaltered wiffle ball (a hollow plastic ball with holes).
 - (2) The angle of the bank board must be no less than sixty degrees off plumb and no greater than seventy degrees off plumb, away from the player. The operator must keep on location a tool to attest to and maintain this standard.
 - (3) A sign must state: "When player hits plastic red zone area with ball, foul shot is created and player loses turn".
- (S) Bushelbasket game. Game shall be played with a ball the same size as a softball. Basket must be a standard bushelbasket of four pecks having a height of at least twelve inches and a diameter of at least eighteen inches at the opening. Basket shall be at an angle of no less than sixty degrees off plumb and no greater than ~~than~~ seventy degrees off plumb away from the player. The operator must keep on location a tool to attest to and maintain this standard. Distance of throw shall be no greater than eight feet from toe line to the basket rim. Rim shots shall be allowed. Baskets shall be securely fastened to the backboard in a manner that they may be easily removed for inspection.
- (T) Tub game. Game shall be played with a ball the same size as a softball. Tubs must

have a height of at least twelve inches and a diameter of at least eighteen inches at the opening. Tubs shall be at an angle of no less than sixty degrees off plumb and no greater than seventy degrees off plumb away from the player. The operator must keep on location a tool to attest to and maintain this standard. Distance of throw shall be no greater than eight feet from toe line to the tub rim. Rim shots shall be allowed. Tubs shall be securely fastened to backboard in a manner that they may be easily removed for inspection.

(U) For purposes of defining standard balls to be used in playing games, the following shall apply:

- (1) Baseball: The ball shall be a sphere formed by yarn wound around a small core of cork, rubber or similar material and covered with two strips of white horsehide or two strips of white cowhide tightly stitched together. It shall be nine to nine and one-half inches in circumference.
- (2) Softball: The ball shall be a sphere formed by either a core of number nine long fiber kapok or yarn wound around a small core of cork, rubber or similar material and covered with a smooth seam stitch which is not visible on a flat surface. It shall weigh not less than six and one-fourth ounces nor more than seven ounces and be eleven and ~~seven-eighths~~ eighths to twelve and one-eighth inches in circumference.
- (3) Football: The weight shall be from fourteen to fifteen ounces and it shall be inflated to a pressure of twelve and one-half to thirteen and one-half pounds. The measurements shall be as follows: long axis is ten and seven-eighths inches to eleven and seven-sixteenths inches; short circumference shall be twenty and three-fourths inches and the long circumference shall be twenty-seven and three-quarter inches to twenty-eight and one-half inches. Method of measuring shall consist of the following: all measurements shall be made after the ball is inflated to thirteen pounds; the long circumference should be measured ninety degrees from lace around the ends of the ball, over the groove but not in the groove; the long axis should be measured from end to end, but not in the nose indentation; the short circumference should be measured around the ball, over the valve, over the lace, but not over a cross-lace.

Effective: 03/23/2017

Five Year Review (FYR) Dates: 01/06/2017 and 03/23/2022

CERTIFIED ELECTRONICALLY

Certification

03/13/2017

Date

Promulgated Under: 119.03
Statutory Authority: 1711.11
Rule Amplifies: 1711.11
Prior Effective Dates: 12/23/1986, 9/02/2005