CSI - Ohio

The Common Sense Initiative

Business Impact Analysis

Agency Name: Ohio Board of Building Standards	
Regulation/Package Title: Ohio Mechanical Code Update	
Rule Number(s): Rescind all existing rules in 4101:2; Adopt new rules 410	<u>1:2-1-01, 4101:2-</u>
2-01, 4101:2-3-01, 4101:2-4-01, 4101:2-5-01, 4101:2-6-01, 4101:2-7-01, 410	01:2-8-01, 4101:2-
9-01, 4101:2-10-01, 4101:2-11-01, 4101:2-12-01, 4101:2-13-01, 4101:2-14-0	<u>01, 4101:2-15-01</u>
Date: January 3, 2017	
Rule Type:	
X New X 5-Year Review	,
Amended X Rescinded	

The Common Sense Initiative was established by Executive Order 2011-01K and placed within the Office of the Lieutenant Governor. Under the CSI Initiative, agencies should balance the critical objectives of all regulations with the costs of compliance by the regulated parties. Agencies should promote transparency, consistency, predictability, and flexibility in regulatory activities. Agencies should prioritize compliance over punishment, and to that end, should utilize plain language in the development of regulations.

Regulatory Intent

1. Please briefly describe the draft regulation in plain language.

Please include the key provisions of the regulation as well as any proposed amendments.

The Ohio Board of Building Standards (Board) proposes to rescind all existing rules in 4101:2 and adopt new Ohio Administrative Code (OAC) Rules as follows:

77 SOUTH HIGH STREET | 30TH FLOOR | COLUMBUS, OHIO 43215-6117 <u>CSIOhio@governor.ohio.gov</u>

BIA p(170946) pa(312264) d: (671562) print date: 07/12/2025 2:39 AM

- **4101:2-1-01:** This proposed rule regulates the administration of the mechanical code by certified building departments.
- **4101:2-2-01:** This proposed rule sets forth the definitions of terms used in rules 4101:2-1 through 4101:2-15-01
- **4101:2-3-01:** This proposed rule contains the requirements for the safe installation of mechanical equipment and appliances.
- **4101:2-4-01:** This proposed rule regulates the quality of indoor air and ventilation.
- **4101:2-5-01:** This proposed rule regulates the installation of exhaust systems to protect against the hazards air contaminants and smoke development in the event of a fire.
- **4101:2-6-01:** This proposed rule regulates the installation of supply, return and exhaust air systems.
- **4101:2-7-01:** This proposed rules sets forth the requirements for combustion air.
- **4101:2-8-01:** This proposed rule regulates the design and installation of chimneys, vents and their connections to rule-burning appliances.
- **4101:2-9-01:** This proposed rule contains the requirements for construction and performance of fireplaces, appliances and solid-burning equipment.
- **4101:2-10-01:** This proposed rule contains the requirements for boilers, water heaters and pressure vessels.
- **4101:2-11-01:** This proposed rule regulates the use of refrigerants and the installation of refrigerating systems.
- **4101:2-12-01:** This proposed rule regulates the construction, alteration and repair of hydronic piping systems.
- **4101:2-13-01:** This proposed rule regulates the design and construction of fuel oil piping and storage.
- **4101:2-14-01:** This proposed rule regulates the design and construction of solar energy systems use for space heating and cooling and domestic hot water heating.
- **4101:2-15-01:** This proposed rule lists technical standards referenced in rules 4101:2-1 through 4101:2-14
- Significant changes to these rules are listed in attached Exhibit A.
- 2. Please list the Ohio statute authorizing the Agency to adopt this regulation.

Revised Code § 3781.10: http://codes.ohio.gov/orc/3781.10 Revised Code § 3781.11: http://codes.ohio.gov/orc/3781.11

3. Does the regulation implement a federal requirement? Is the proposed regulation being adopted or amended to enable the state to obtain or maintain approval to administer and enforce a federal law or to participate in a federal program?

If yes, please briefly explain the source and substance of the federal requirement.

4. If the regulation includes provisions not specifically required by the federal government, please explain the rationale for exceeding the federal requirement.

Not applicable.

5. What is the public purpose for this regulation (i.e., why does the Agency feel that there needs to be any regulation in this area at all)?

Revised Code § 3781.10 directs the Board to "formulate and adopt rules governing the erection, construction, repair, alteration and maintenance of all buildings specified in section 3781.06 of the Revised Code..." Additionally, Revised Code 3781.06 provides:

Any building that may be used as a place of resort, assembly, education, entertainment, lodging, dwelling, trade, manufacture, repair, storage, traffic, or occupancy by the public, any residential building, and all other buildings or parts and appurtenances of those buildings erected within this state, shall be so constructed, erected, equipped, and maintained that they shall be safe and sanitary for their intended use and occupancy.

This statute defines safe and sanitary as follows:

"Safe," with respect to a building, means it is free from danger or hazard to the life, safety, health, or welfare of persons occupying or frequenting it, or of the public and from danger of settlement, movement, disintegration, or collapse, whether such danger arises from the methods or materials of its construction or from equipment installed therein, for the purpose of lighting, heating, the transmission or utilization of electric current, or from its location or otherwise.

"Sanitary," with respect to a building, means it is free from danger or hazard to the health of persons occupying or frequenting it or to that of the public, if such danger arises from the method or materials of its construction or from any equipment installed therein, for the purpose of lighting, heating, ventilating, or plumbing.

The Ohio Building Code sets forth the construction standards for nonresidential buildings in the State of Ohio to ensure that they are safe and sanitary. Additionally, Revised Code § 3781.01 provides that local governments may not adopt regulations that that conflict with the Board's rules to facilitate the uniform application of the standards.

Revised Code 3781.11 lists conditions that rules of the Board must address, including:

77 SOUTH HIGH STREET | 30TH FLOOR | COLUMBUS, OHIO 43215-6117 CSIOhio@governor.ohio.gov

- (1) For nonresidential buildings, provide uniform minimum standards and requirements, and for residential buildings, provide standards and requirements that are uniform throughout the state, for construction and construction materials, including construction of industrialized units, to make residential and nonresidential buildings safe and sanitary as defined in section 3781.06 of the Revised Code;
- (2) Formulate such standards and requirements, so far as may be practicable, in terms of performance objectives, so as to make adequate performance for the use intended the test of acceptability;
- (3) Permit, to the fullest extent feasible, the use of materials and technical methods, devices, and improvements, including the use of industrialized units which tend to reduce the cost of construction and erection without affecting minimum requirements for the health, safety, and security of the occupants or users of buildings or industrialized units and without preferential treatment of types or classes of materials or products or methods of construction;
- (4) Encourage, so far as may be practicable, the standardization of construction practices, methods, equipment, material, and techniques, including methods employed to produce industrialized units;

6. How will the Agency measure the success of this regulation in terms of outputs and/or outcomes?

The enforcement of these rules will be implemented by certified township, city, and county building departments. Rule 4101:1-1-01 lays out the administrative procedures certified building departments must follow to implement the substantive requirements of these rules to determine compliance. These provisions require a builder or owner to make application to a building department to obtain an approval to build (permit). As part of this application the owner must submit sufficient information and/or construction documents for the building official/plans examiner to determine whether the proposed work complies with the code. After the builder or owner obtains the approval (permit), construction may commence and the building department inspectors will inspect the construction to ensure that the work conforms with the original approval. Rule 4101:1-1-01 § 105.2 provides that in the absence of fraud or a serious safety or sanitation hazard, any non-residential structure built in accordance with approved plans shall be conclusively presumed to comply with these rules. The Board requires that certified nonresidential building departments submit an annual yearly operational report which lists the following information: current employees and their certifications, total number of permits issued during the year for each type of occupancy,

total number of inspections made, the total value of construction, and the total number of appeals of the code requested by a builder or owner during the year.

Development of the Regulation

7. Please list the stakeholders included by the Agency in the development or initial review of the draft regulation.

If applicable, please include the date and medium by which the stakeholders were initially contacted.

The Board maintains a stakeholder distribution including building department personnel, contractors, designers and professional associations. The stakeholder list is available upon request. On October 7, 2016, the Board sent an email to all agency stakeholders informing them of a scheduled stakeholder meeting on October 28, 2016 to hear comments and respond to questions on these rules. The notice summarized the proposed amendments and also informed stakeholders that if they could not attend the stakeholder meeting, they could submit questions or comments via email or regular mail by November 2, 2016. On October 28, 2016, the Board conducted a stakeholder meeting on the proposed rules at 2:30 PM. No stakeholders attended but written comments were submitted by Michael Miller, Cincinnati Financial.

8. What input was provided by the stakeholders, and how did that input affect the draft regulation being proposed by the Agency?

A copy of the correspondence the Board received in response to October 7, 2015 email are attached as Exhibit B. The initial comments received were reviewed by the Board's Code Committee at its November 3, 2016 and December 8, 2016 meetings. The Board's Code Committee reviewed Mr. Miller's comments and in response corrected the definition of boiler

9. What scientific data was used to develop the rule or the measurable outcomes of the rule? How does this data support the regulation being proposed?

The proposed rules are based on the 2015 International Mechanical Code (IMC) promulgated and amended by the International Code Council (ICC). The model codes developed by ICC are updated every three years through a process that incorporates petitioning, public hearings and voting by ICC members. The ICC Committees that oversaw the development of the different provisions 2015 IMC included building and fire code officials, engineers, mechanical contractors, boiler inspectors and the National Association of Home Builders.

When a petition to amend the model code is submitted, the proponent of the change must submit the proposed language of the amendment, the reason for the amendment including

scientific data when applicable, and the cost impact of the amendment. All submitted petitions are then published prior to initial code development hearings on the petitions. Interested persons may review the proposed changes and attend the code development hearing and provide comments. A report then is published on the public hearings for review and then final action is taken on the proposed changes at final action hearings. All successful changes are incorporated into the next edition of the model code.

Upon publication the Board's code committee reviews each substantive change included in the newest edition of the code and determines whether to recommend the change to the Board for adoption. The Board last fully updated the OMC on November 1, 2011.

10. What alternative regulations (or specific provisions within the regulation) did the Agency consider, and why did it determine that these alternatives were not appropriate? If none, why didn't the Agency consider regulatory alternatives?

See Question 9.

11. Did the Agency specifically consider a performance-based regulation? Please explain.

Performance-based regulations define the required outcome, but don't dictate the process the regulated stakeholders must use to achieve compliance.

The rules permit a registered design professional's alternative engineered design to be a compliance alternative method to the prescriptive requirements of the code. Section 106.5 of the Ohio Building Code permits a registered design professional to submit sufficient technical data to substantiate that performance of the proposed alternative engineered design meets the intent of the code. Additionally, section 107.4.3 provides that when construction documents have been prepared by an Ohio registered design professional conforming to the requirements of the rules of the Board pertaining to design loads, stresses, strength, and stability and other requirements involving technical analysis, the documents need only be examined to the extent necessary to determine conformity with other requirements of the rules of the Board.

12. What measures did the Agency take to ensure that this regulation does not duplicate an existing Ohio regulation?

Editorial changes are routinely made to the rules to provide consistency with the Ohio Revised Code and other Board and agencies' rules. Additionally, RC § 3781.10 gives the Board sole authority to adopt rules which regulate the erection, construction, repair, alteration, and maintenance of all buildings or classes of buildings specified RC 3781.06 including residential and non-residential buildings.

13. Please describe the Agency's plan for implementation of the regulation, including any measures to ensure that the regulation is applied consistently and predictably for the regulated community.

For these rules to be enforced by a local government, its building department must be certified by the Board. The Board also certifies the personnel who work within these departments to ensure only qualified personnel are enforcing the Board's rules. Certified personnel must complete continuing education to maintain their certifications and continue to be authorized to enforce these rules. The Board has authority to suspend or revoke certifications for failure to properly enforce the rules. Also, the Board has a staff member dedicated to responding to complaints by persons affected by the Board rules. This program helps promote consistent and predictable application of the Board rules.

Adverse Impact to Business

- 14. Provide a summary of the estimated cost of compliance with the rule. Specifically, please do the following:
 - a. Identify the scope of the impacted business community;
 - Building owners
 - Design Professionals
 - Contractors
 - Building Department Personnel
 - b. Identify the nature of the adverse impact (e.g., license fees, fines, employer time for compliance); and
 - Obtaining updated rules as published as the Ohio Mechanical Code
 - Becoming familiar with the changes through research and training
 - Increased cost of construction due to changes that require different construction methods/materials/products or increased stringency of construction standards.
 - c. Quantify the expected adverse impact from the regulation.

The adverse impact can be quantified in terms of dollars, hours to comply, or other factors; and may be estimated for the entire regulated population or for a "representative business." Please include the source for your information/estimated impact.

Due to the variance in allowed building designs, it is difficult to ascertain, in dollars, a cost increase/decrease in the design cost of a building as a result of the proposed code update. However, as discussed in Question 9 above, when a code change proponent submits a petition to ICC to amend the model code an estimated cost impact of the

proposal is included. Of the significant changes, the following sections included in the proposed rules were noted by the proponent as having a cost increase in construction:

Section 306.1 – Clarifies that controls, heat exchangers, and other energy using HVAC equipment needs to be accessible.

Section 307.2.5 – Add requirement to enable clearing drain without cutting line.

Section 307.3 – Requires that appliance shut off when condensate pump fails

Section 401.2 – Requires mechanical ventilation for dwelling units when air infiltration rate is less than 5 ACH as determined by blower door test.

Section 404.1 - Allows parking garage ventilation systems to be intermittently operated by CO and NO2 detectors.

Section 506.3.7.1 – Modified to extend full width of the duct.

Section 506.5.3 – Clarifies that up-blast fans shall be equipped with a means of restraint to limit the fan swing.

Section 507.1 – Reorganized entire section and added scoping paragragh.

Section 507.1.1.1 – Added a section addressing multiple hoods utilizing a single exhaust system.

Section 510.5 – Separated out the requirements for incompatible materials by creating a separate section and added a few new conditions for laboratory exhaust systems.

Section 602.1 – Requires ducting from the boundary of the fire area to the air handling equipment.

Section 602.2 – Clarifies that construction materials that are exposed to the airflow are subject to the plenum requirements.

Section 602.2.1.5 – Adds a new section for discreet plumbing and mechanical products in plenums.

Section 1101.10 – Allows other options for securing refrigerant caps.

Section 1102.3 – Requires access port protection when refrigerant is added or recovered.

Section 1105.6.3 – Adds a new section for ventilation rate of refrigeration systems.

The new Ohio Mechanical Code publication will be available from publishers at an approximate cost of \$100.

15. Why did the Agency determine that the regulatory intent justifies the adverse impact to the regulated business community?

While noted as cost increase, many of the changes listed have little or no affect depending on the design choices. The most significant is Section 401.2 requirement for mechanical ventilation. This change is offset for certain residential occupancies by permitting the owner to comply with energy code requirements in the Residential Code of Ohio. Additionally, other changes included

in the rule package will decrease cost of construction, offer regulatory alternatives, and recognize new technologies and materials.

Finally, until the current edition the Board updated the codes every three years. The Board has taken steps to lengthen the time between code updates to reduce the impact on the construction community. To date, however, 14 states have already adopted the 2015 IMC and another 17 have adopted the 2012 IMC. Projects are designed months and years in advance. Design professionals need predictability to be able to design the appropriate standards. This update will keep Ohio's code aligned with the majority of other states.

Regulatory Flexibility

16. Does the regulation provide any exemptions or alternative means of compliance for small businesses? Please explain.

The rules do not have special exemptions or alternative means of compliance specifically for small business. The Ohio Building Code (OBC) requires a building official to issue an adjudication order to an owner when the design or construction of a building does not comply with the OBC. The adjudication order must comply with Revised Code Chapter 119 and give the owner an opportunity to appeal. This mechanism is often utilized by an owner voluntarily to obtain a variance from the requirements. Variance requests are heard by either the Ohio Board of Building Appeals or a certified local board of building appeals.

Also, the OBC permits alternative engineered designs prepared by a registered design professional to not strictly comply with the prescriptive requirements of the rules. To obtain approvals based on alternative engineered designs, the design professional must submit sufficient technical information to demonstrate that the performance meets the intent of the rules.

17. How will the agency apply Ohio Revised Code section 119.14 (waiver of fines and penalties for paperwork violations and first-time offenders) into implementation of the regulation?

Revised Code § 3781.102 does not authorize the Board to set the fees and/or penalties assessed by local certified residential building departments in connection with the enforcement of these rules. Compliance with the rules is accomplished through construction conforming to the certificate of plan approval (permit). Therefore, there are no potential paperwork violations of these rules.

18. What resources are available to assist small businesses with compliance of the regulation?


As these proposed rules updates the Ohio Mechanical Code to a new model code edition, the Board offers training and resources to building department personnel to prepare them to enforce the new codes. These resources are paid for by assessment fees collected by certified building departments pursuant to RC 3781.102 on behalf of the Board to be used exclusively for (1) the operating costs of the Board, (2) providing services, including educational programs, for building departments certified by the Board, and (3) paying the expenses of the Residential Construction Advisory Committee.

Additionally, the Board's technical staff spends approximately 25% of their time responding to questions on the building codes and educating design professionals, contractors, the public, and code officials of the intent of the Board's rules assisting all parties in compliance.

Summary of BBS Proposed Ohio Mechanical Code Rule Changes - October 2016

Significant Changes are highlighted in yellow

Ohio Administrative	OMC Section	IMC change	Reason for proposed
Code Rule Number		origin	change
4101:2-2-01	Air, Makeup	2015	Modified definition
	Air, Outdoor	2015	Added definition
	Air, Transfer	2015	Added definition
	Clothes Dryer	2012	Modified definition to
			remove Types
	Combustible Liquid	2012	Modified definition
	Commercial Cooking	BBS initiated	Modified definition to
	Appliances	change	clarify intent
	Commercial Food	BBS initiated	Modified definition to
	Service Establishment	change	clarify intent
	Conditioned Space	2015	Modified definition
	Design Flood Elevation	2015	Modified definition
	Discrete Product	2015	Added definition
	Domestic Cooking	BBS initiated	Added definition
	Appliances	change	Traded definition
	Ductless Mini-Split	2015	Added definition
	System		raded definition
	Environmental Air	2012	Modified definition to
			include parking garage
			exhaust
	Exfiltration	2015	Added definition
	Extra-Heavy-Duty	2015	Modified definition
	Cooking Appliance	On discontinuo	
	Flammability	2015	Moved definition from
	Classification	OF THE STATE OF TH	Refrigerant Safety
			Classification
	Flexible Air Connector	2015	Added definition
	Heavy-Duty Cooking	2015	Modified definition to
	Appliance		add smokers and
			smoker ovens
	Household Cooking	BBS initiated	Added definition
	Appliances	change	
	Infiltration	2015	Added definition
	Lower Flammable Limit	2012	Modified definition
	Mechanical Joint	2012	Modified definition
	Occupational Exposure	2015	Added definition
	Limit		
	Press Joint	2012	Added definition
	Protective Assembly	2015	Modified definition
	(Reduced Clearance)		delinition
	Refrigerant Safety	2015	Moved part of
	Classification		definition



	Toxicity Classification	2015	
Out of Annual Property of Annual	Toxicity Classification	2015	Moved and modified
	Will be a second of the second	on and a second	definition from
		entre	Refrigerant Safety
4101:2-3-01	302.2		Classification
7101.2-3-01	302.2	2012	Added a reference to
	202.2		OBC Chapter 7
	303.3	2015	Modified exception #2
		and the second s	to remove reference to
Verando de la companya del companya de la companya del companya de la companya de		THE PROPERTY OF THE PROPERTY O	unusually tight
			construction
	304.3	2012	Added an exception to
naconardo de la composição de la composi			the requirement to
		and the second s	elevate the ignition
			source
	304.5	2012	Added a sentence
			requiring compliance
			with listing and
			manufacturer's
		9999	instructions
	304.11	2015	Clarified guard
		THE STATE OF THE S	requirements and added
		THE CONTROL OF THE CO	an exception for guards
			if fall-arresting restraint
			system is provided
	305.4	2015	Changed referenced
	***************************************	-0.0	standard to MSS SP-58
	306.1	2015	Clarifies that controls,
			heat exchangers, and
		1992 AND CO.	other energy using
	NAME AND ADDRESS OF THE PARTY O	montanana de la companio de la compa	HVAC equipment
			needs to be accessible
	306.5	2012	Modified access
		2012	
			requirements for
	306.5.1	2015	appliances on roofs
		2013	Changed stairs to
	307.2	2015	stairways
	201.00	2013	Added an exception for
		er de la companya de	condensate drain
	307.2.2	2015	requirement
	307.2.2	2013	Removed polybutylene
			and added
			polypropylene for drain
	307.2.4.1	2015	pipe
	307.2.4.1	2015	Adds requirement for
		PO CONTRACTOR CONTRACT	inline check valve for
		POLINICATION AND ADDRESS AND A	ductless mini-split
	207.2.5		condensate drain
	307.2.5	2015	Adds requirement to
			enable clearing drain

			without cutting drain
			line
	307.3	2015	Requires that applianc shut off when
			condensate pump fails
	308.5	2012	Added a reference to UL 1618
4101:2-4-01	401.2	2012	Requires mechanical
		Military	ventilation for dwelling
			units when air
			infiltration rate is less
			than 5 ACH as
			determined by blower
			door test
	401.4	2012	Clarified intake
			opening location
	**************************************	iki insansaaya	requirements
	401.5	2012	Adds referenced
	**		standard AMCA 550
	NO STATE OF THE ST		for louvers in
	of Contract of Con	amen and an	
	403.1	2015	hurricane-prone regions Clarifies that
		2015	mechanical ventilation
	Polyment and the second	days	
		77/7	air requirements for
		9-19-1-1-19-1-1-19-1-1-19-1-1-19-1-1-19-1-1-19-1-1-1-19-1-1-1-19-1-1-1-1-1-1-19-1	dwelling units is met
			via an exhaust system,
			supply system, or a combination of both.
	403.2	2015	Relocated a sentence to
		2015	Section 403.3.1.1
	403.2.1, items #3 and #4	2015	Clarified that
		2013	recirculation of air
	***	and of the state o	
		70 70 70 70 70 70 70 70 70 70 70 70 70 7	within a space is permitted, but not from
			0.000
	403.3	2015	Clarified ventilation
		2013	requirements for
	Table 403.3	2012	dwelling units
		2012	Rearranged the columns
	Table 403.3	2012	
	1 1010	2012	Broke out nail salons as
			a separate row and
			clarified that a source
			capture system is
	Table 403.3	2012	required
	403.3.2		Clarified notes e and f
	103.3.2	2015	Clarified ventilation
			requirements for
			dwelling units

	404.1	2015	Allows parking garag
	and the same of th		ventilation systems to
	No. of the Control of		be intermittently
	ROST 1-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2	troit voice	operated by CO and
4101:2-5-01			NO2 detectors.
4101:2-5-01	501.2	2012	Added a new section
	1944		clarifying that certain
			exhaust systems need
			to be independent
			systems
	501.3	2015	Relocates the
	d or an analysis		prohibition of
	Noneman de la companya de la company		exhausting air onto
	900-000-000-000-000-000-000-000-000-000		walkways from Section
			501.3.1.1
	501.3	2015	Clarifies that listed
	1-Accommonsories		domestic ductless rang
	Of the state of th		hoods are not required
			to exhaust to the
			outdoors
	501.3.2	2012	Adds referenced
	PETERSON	- Order and a second a second and a second a	standard AMCA 550
			for louvers in
			hurricane-prone region
	502.8.1	2012	Adds ventilation
	Treasing Annual Property Control of the Control of		requirement for
			fireworks and
			explosives storage
			areas and storage
	5050		buildings
	502.9.1	2012	Exhaust system
	of contrast	and the second s	thresholds for
	Porime MANALA		compressed gases now
	The second secon		based upon permit
	THE ACTION OF TH		amounts in the IFC, not
	APPEN AND AND AND AND AND AND AND AND AND AN		maximum allowable
	502.0.11		quantities
	502.9.11	2012	Reference to IFC
			Chapter 64 for Silne
	and the second s		gas exhausted
			enclosure and gas
	502.10.2	2012	cabinet requirements
	302.10.2	2012	Clarified exhaust duct
			penetration
	502.14	20:	requirements
	302.14	2015	Add requirement for
			registered design
			professional
			engineering or factory
			built equipment

	7.00.00		
	502.20	2015	Adds a new section for
	uron.	To the second se	manicure and pedicure
			exhaust systems
	504.5	2015	Adds a new section for
And the second s	MACAAAA	Anne	dryer exhaust duct
			power ventilators
To deliver the second s	504.7	2015	Relocated from section
		TO A CALLES	504.6.7
	504.8	2012	Removed reference to
			Type 2 clothes dryer
disability resident	504.8.2	2015	Clarifies that screw
		The second secon	protrusion of not more
			than 1/8 inch is
		man and the state of the state	permitted
	504.8.4.3	2015	Adds a new section for
	distribution and the second se		dryer exhaust duct
			power ventilators
	504.10	2012	Adds an additional
		Similar Turk St. St. Similar	condition for multi-
			1
	nuclear constant	ATT TO THE STATE OF THE STATE O	story dryer duct system independence
	505.1	BBS initiated	Adds new first sentence
	000.1	change	
	505.1	2012	to clarify scope
	303.1	2012	Adds an independence
	33000		requirement for
			domestic kitchen
	505.1	2015	exhaust ducts
	303.1	2015	Removes reference to
	505.1		dwelling units
	505.1	BBS initiated	Added exception 1 to
	505.3	change	clarify intent
	505.3	2015	Added a new section
	Will Andrew or or	oo kaasaa ka k	for common exhaust in
	P () W		a multi-story building
	505.4	BBS initiated	Deleted section
		change	
	505.5	BBS initiated	Clarified Group I-2
		change	requirements
	506.3.2.3	2012	Requires 1500 F rating
			for gaskets and seals of
			duct-to- exhaust fan
			connections
	506.3.7.1	2012	Adds new criteria for
			grease duct reservoirs
	506.3.7.1	2015	Modified condition #3
			to extend the full width
			of the duct
	506.3.8	2012	Breaks the cleanout
			requirements into a list
			and adds a 1500 F
			and adds a 1500 F

			-
			rating requirement for gaskets and seals
	506.3.8	2015	
oo aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa	300.3.8	2015	Adds dimensions to
	506.3.9	2010	condition #2
	300.3.9	2012	Breaks the horizontal
	To common and the com		cleanout requirements
	506.3.10	BBS initiated	into a list
	300.3.10		Relocated underground
	oden de la companya d	change –already	grease duct
	110-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	adopted 2012 text	requirements from
	506.3.11	2012	506.3.13
vanish (Alice Control of Control	300.3.11	2012	Duct enclosure rating
			shall be consistent with
			the rating of the
			assembly penetrated,
	5063.11		not less than 1 hour.
	506.3.11	2015	Relocates 506.3.11.4 to
The state of the s	No. of the state o		a new exception in
	50(2.11		506.3.11
	506.3.11	2015	Clarifies that an
e a colonia	WOAD PROCESS		enclosure is only
nonese reprodu	3 ROOM (1975)		required for
			commercial grease
The opposition of the state of			ducts, that in-line fans
		and the second s	shall be enclosed unless
Verenza de la constanta de la	MCGRATIC CONTROL OF THE CONTROL OF T		outdoors, and that fire
	10000000000000000000000000000000000000		and smoke dampers are
			not permitted in grease
	506 2 11 2	10010	ducts
	506.3.11.2	2012	Prohibits partial
	***************************************		application of field-
			applied duct enclosure
	506 2 11 2	2015	systems
	506.3.11.2	2015	Corrects the UL
	506.3.11.3	2015	standard number
	300.3.11.3	2015	Clarifies that the duct
			enclosure assembly and
	THE PROPERTY OF THE PROPERTY O		firestop system needs
			to be installed in
			accordance with its
			listing and
			manufacturer's
	506.3.13.3	2012	instructions
	300.3.13.3	2012	Adds the word
			"horizontally" to
	506.4	2012	clarify intent
	506.4	2012	Relocates a
			requirement for Type II
			exhaust system
			independence to 501.2

506.5.1.2	2015	Adds a new section for
	1	in-line fans
506.5.3	2015	Clarifies that up-blast
	weeters of the second s	fans shall be equipped
	over the second	with a means of
	Asymmune asy	restraint to limit the
	Transmission of the Control of the C	swing of the fan
507.1	2012	Reworded to clarify
		intent
507.1	2015	Reorganized entire
		section 507 and added
		scoping paragraph
507.1.1	2012 and 2015	Clarified interlock
	460)	methods
507.1.1.1	2015	Added a section
	Visitoria de la companya de la compa	addressing multiple
		hoods utilizing a single
	100.00	exhaust system
507.2	BBS initiated	Removed list of
	change	appliances requiring
		hoods
507.2	2012	Added an exception to
		the requirement for a
		Type I hood
507.2.1	2012	Requires flow rate label
		on Type I hoods
507.2.7	2012	Clarified that field-
		applied grease duct
		enclosure systems are
	90101	not to be used to
		protect hoods that
	The state of the s	penetrate ceiling, wall
		or furred spaces
507.2.8	2012 and 2015	Added UL 1046
		standard for grease
		filters
507.3	2012	Clarifies when Type II
		hoods are required and
		adds a minimum
		exhaust rate for spaces
		that contain cooking
500 1 2		appliances but no hood
508.1.2	2015	Requires air balance
		schedule for the
		commercial kitchen
510.5		ventilation system
510.5	2015	Separated out the
		requirements for
		incompatible materials
		by creating a separate

	**************************************	section and added a
	THE THE STATE OF T	few new conditions for
		laboratory exhaust
		systems
510.5.5	2015	Clarified that make-up
		air is required to
		comply with 401.4.
510.7.1.1	2015	Provides a reference to
		specific OBC sections
	NO. SECTION AND ADDRESS OF THE PROPERTY OF THE	to address shaft
	ODDINA SERVICE	penetrations of
		hazardous ducts
510.8	2012	Added a suppression
	en e	exception for non-
	**************************************	combustible hazardous
		ducts in semiconductor
	The state of the s	fabrication facilities
510.9	2015	Reorganized the
		section
510.9.1	2012	Allows hazardous duct
	Au O 2 Jus	i i
	deleteration	joints complying with
513.4.6	2015	SMACNA standards
313.7.0	2015	Changed "passive" to
	4111	"engineered" smoke
	Na Arian de Carlos de Carl	control and changed
	ol are in the second	"whichever is less" to
513.4.7	2015	"whichever is greater"
313.4.7	2015	Requires the
	The real section of the section of t	consideration of all
		other smoke control
513.5	2015	systems in the design
313.3	2015	Clarifies that smoke
		barriers are used for
	To the second	passive smoke control
E10 E		systems
513.5	2012	Changed "Exit
	To a second seco	enclosures" to "Interior
	of many	exit stairways and
		ramps and exit
		passageways" and "All
		other shafts" to
		"Enclosed exit access
		stairways and ramps
		and all other shafts"
513.5.2	2015	Added exceptions for
		Group I-1 and
		Ambulatory care
		facilities
513.5.3.1	2015	Adds a new section
		addressing Group I-1,

No photogram	a contract of the contract of		I-2, and Ambulatory
	513.6.3	2015	Care Facilities
	313.0.0	2013	Adds a new section for
	decourse and the second		pressurized stairways
	513.7	0017	and elevator hoistways
	313.7	2015	Adds a reference to
		Of the state of th	NFPA 92 when using
	513.11		the airflow method
	313.11	2015	Clarified standby
			power requirements for
	512.12.1		smoke control systems
	513.12.1	2015	Provides an exception
	16 of a constant		to the verification
			requirement
	513.13.1	2012	Requires tubing to
	***************************************		comply with OMC
	***************************************	DO (1)	Section 602.2.1.3
			(listed/labeled, flame
			spread and optical
			density requirements)
	514.1	2012	Adds standards for
	en e		listing and labeling of
	TO STATE OF THE ST		heat recovery
	***************************************		ventilators
	514.2	2015	Allows ERV
	THE PARTY OF THE P		equipment that
	electronismos		recovers sensible heat
			only utilizing coil-type
		display	heat exchangers
	514.4	2012	Clarifies how
			recirculated air is
	Wilderman		considered in the
	****		context of energy
	No. of the Control of		
101:2-6-01	601.4	2012	recovery systems
	- CONTRACTOR CONTRACTO	2012	Adds an exception for
	Other productions		chimneys and vents
	111	OL COMMISSION OF THE PROPERTY	passing through
	601.5	2015	plenums
	001.5	2013	Relocates section
			addressing return air
			openings from Chapter
	602.1	2015	9
	002.1	2015	Requires ducting from
			the boundary of the fire
			area to the air handling
	602.2	200.5	equipment
	602.2	2015	Clarifies that
			construction materials
			that are exposed to the
			airflow are subjected to

			. 1
PORTOLOGICA		n a garage	the plenum
	(22.2.1		requirements
	602.2.1	2012	Clarifies that materials
	Control of the Contro		within a plenum must
	Assetional		be listed and labeled if
			combustible
	602.2.1.1	2012	Clarifies the
	OFFICE AND ADDRESS OF THE ADDRESS OF		requirements for
			combustible optical
	A-		fiber within plenums
	602.2.1.5	2015	Adds a new section for
of the second se			discreet plumbing and
The second secon			mechanical products in
The second secon			plenums
	602.2.1.6	2012	Adds a new section for
No.	002.2.1.0	2012	
oos uprami adolo			foam plastic insulation
	602.2.1.7	2015	in plenums
ma secondo	002.2.1.7	2015	Adds a new section for
	and the second s		plastic plumbing pipe
	600.0		and tubing in plenums
The second secon	603.2	2015	Allows manufacturer's
Transfer of the Control of the Contr	TO CONTRACT OF THE CONTRACT OF		installation instructions
	Taran and the same of the same		to be used for sizing
	22		dwelling unit ducts
	Table 603.4	2015	Modifies the minimum
			duct thickness table
	603.4.2	2015	Adds a new section for
			duct lap
	603.9	2015	Changes "Closure
			systems" to "Tapes and
			mastics" and adds an
			exception for sealing
			certain types of duct
			joints
	603.10	2012	
	003.10	2012	Allows duct supports in
			accordance with the
	603.17	2012	SMACNA standard
	003.17	2012	Adds a new section for
	605.1	2017	air dispersion systems
And the second s	605.1	2015	Clarifies that all air is
от поставления и поста			filtered upstream of a
			heat exchanger or coil
Tanana and a same and	607.1.1	2015	Allows horizontal ducts
The state of the s			connecting shaft
and the state of t			enclosures to not be in
of the state of th			an enclosure if a
			damper is provided
	607.3.1	2015	Adds requirements for
			corridor dampers
			Corridor dumpers

	1 (07 0 0 0		
	607.3.2.3	2012	Modified the
	VV de la commanda	Name of the Control o	combination fire/smoke
			damper requirements
	607.3.3.2	2015	Clarifies that duct
**************************************			smoke detectors can be
			outside of the duct if
TOTAL CONTRACTOR OF THE CONTRACTOR OF T		**************************************	the sampling tubes
Action in the second se	Proposition of the Control of the Co		protrude into the duct
	d) for several		and requires detectors
			used to activate the
	4	THE STATE OF THE S	smoke damper be listed
			for releasing service
	607.5	2015	Adds reference to
	000		ceiling radiation
		Pil de de la constante de la c	dampers
	607.5.2	BBS initiated	Clarified when flexible
Terret	Autorities and Autori	change	air connectors can be
			used in fire barriers
Approximation and the second and the	607.5.3	2012	Added new exception
			for ducted HVAC
	of the same of the		systems
	607.5.3	BBS initiated	Clarified when flexible
T-Al-A-Commence	Parameter State Control of the Contr	change	air connectors can be
		onange	used in fire partitions
	607.5.4	2015	Clarifies when corridor
		2013	
		No. 4 Principles	vs ceiling radiation
	to considerate of the constant	NATION OF THE ASSESSMENT OF TH	dampers are required
	name v	100	and adds an exception
		**************************************	for smoke dampers in
	607.5.5	BBS initiated	certain smoke barriers
	007.5.5	change	Added new exception
	Commission	Change	for smoke dampers in
4101:2-7-01	701.2	2015	sprinklered buildings
	701.2	2015	Adds a new section
		TO CONTRACTOR OF THE CONTRACTO	requiring interlocks for
4101:2-8-01	801.16.1	2010	dampered openings
	301.10.1	2012	Requires labeling of
			listed chimney lining
	802.9	2015	systems
	802.9	2015	Adds a 12 inch
			horizontal vent
			terminal clearance from
	904.2		door swings
	804.3	2012	Requires listing and
			labeling of mechanical
			draft systems in
			accordance with UL
			378
	804.3.8	2012	Requires listing and
			labeling of mechanical

			draft systems in
			accordance with UL
	005.0		378
	805.3	2012	Clarifies requirements
	The state of the s		for factory-built
4101 2 0 01			chimney offsets
4101:2-9-01	902.2	2012 and 2015	Adds a labeling
	en e		requirement and
	**************************************		reference to UL 907 for
			fireplace accessories
	903.2	2012	Adds a reference to UL
			1618
1.00 (Commonwealth	903.4	2015	Adds a new section for
		All delications are also as a second	fireplace doors
	905.3	2012	Adds a reference to UL
	THE THE PARTY OF T		1618
	908.1	2012	Adds a reference to
		2012	UL1995
	908.5	2015	Adds additional
		2013	requirements for
	100 a 2 a 2 a 2 a 2 a 2 a 2 a 2 a 2 a 2 a		
	overage (cooling tower water
	908.8	2015	supplies
	700.0	2013	Adds requirements for
	The second secon		cooling tower controls
	911.1	2012	and drift eliminators
	711.1	2012	Changes standard to
	912.1	2010	UL 19996
	714.1	2012	Adds a reference to UL
	918.5	2015	499
	910.3	2015	Provides pointer to
	Name and address of the Control of t	111111111111111111111111111111111111111	other sections for
	el accident		outdoor intake and
	019.6		return air openings
	918.6	2012	Clarifies the garage
	dinas i playe		prohibited source for
			forced air heating and
	010.6		cooling systems
	918.6	2015	Relocates the
			prohibited source
			section to 601.5
	922.1	2012	Adds a reference to
			NFPA 31
	923.1	2012	Adds a reference to UL
			499
	923.1	2015	Adds a reference to
			alternative engineered
			designs.
	927	2012	Adds a new section for
			radiant heating systems
			1 - admin incuting systems

	928	12012	
	920	2012	Adds a new section for
	time constant	00.000	evaporative cooling
	928.1	2016	equipment
	928.1	2015	Adds a condition for
	mu mayoria da	d co	evaporative cooling
de di Proposona	1000	minor de la companya	equipment water
4101:2-10-01	10011		supply
4101.2-10-01	1001.1	BBS initiated	Clarified applicability
	100:0	change	of Chapter 10
**************************************	1001.2	BBS initiated	Clarifies enforcement
		change	responsibilities for
			boilers, pressure
	Windows and a second se		vessels, and hot water
			heaters
	1002.1	2012	Adds standards for
	STATE OF THE PARTY		solid -fuel -fired water
	Objection and the state of the	marks and a second seco	heaters and thermal
			solar water heaters
	1003.1	2015	Clarified the applicable
	омносенно.		construction standard
			for pressure vessels
	1003.3	2015	Clarified the applicable
	or of the state of	en station	construction standard
			for welding of pressure
		11000	vessels
	1004.1	BBS initiated	Allows the ASME
	The state of the s	change	CSD-1 as an option for
	***	-	the design of the boiler
			control system
	1004.1	2012	Adds a standard for
		***	solid-fuel-fired boilers
	1004.1	2015	Clarified boiler design
			standards
	1004.3.1	2012	Reorganizes the boiler
	an utilization		top clearance
100		4	requirements
	1007.1	2015	Adds an exception for
			the low-water cutoff
			control
	1007.2	2015	Adds a requirement
			that combustion
			operations stop when
			water circulation stops
	1008.1	2015	Changed the steam
			boiler blowoff valve
			arrangement
	1009.2	2015	Requires expansion
	- 10 mm		tanks for systems
			operating in excess of
			30 psi to be
			20 har to ac

	The second		construction in accordance with ASMI BPVC
	Table 1009.2	2015	Adds a new table for closed-type expansion tank sizing
	1011.1	2015	Allows tests to be conducted IAW manufacturer's requirements
4101:2-11-01	1101.10	2012	Allows other options for securing refrigerant
	1101.10	2015	Adds an exception for locking access port
	1102.3	2015	caps Requires access port protection when refrigerant is added or recovered
	Table 1103.1	2012	Updates the refrigerant classification table
	1104.1	2015	Deletes last sentence relating to worst case
	1105.6.3	2012	of fractionation Adds a new section for ventilation rate of
	1105.9	2015	refrigeration systems Clarifies that the section only applies to permanently installed
	1106.3	2015	refrigeration systems Corrects reference to 1105.6.3
	1106.4	2012	
	1106.5	2012	Clarifies exception Clarifies control requirements
	1106.5.1	2015	Allows a tamper- resistant cover instead of a break-glass switch
	1106.5.2	2015	Allows a tamper- resistant cover instead of a break-glass switch
	1107.1	2015	Adds a reference to ASME B31.5 for refrigerant piping design
101:2-12-01	Table 1202.4	2012	Adds a standard for PE and PE-RT pipe

A CONTRACTOR OF THE CONTRACTOR	Table 1202.4	2015	Removes brass, PB,
	T-11, 1000 f		and PE pipe and tubing
	Table 1202.5	2012	Adds standards for
			PEX fittings
	Table 1202.5	2015	Removes brass and
	1203.3.4		bronze fittings
eli concentrativo de la concentrativo della concentrativo de la concentrativo della co	1203.3.4	2012	Adds an exception for CPVC pipe joint
			primer
	1203.8	2012	Recognizes press-joints
on de la companya de	1203.15	2015	Removes PE pipe and
			tubing
	1208.1	2015	Relocated testing
			requirements for
	on control of the con		ground source heat
			pump loop systems
	1209.3.2	2015	Removed brazing filler
			metal melting point
			temperature
	1209.3.4	2015	Added a section for
			PE-RT piping
	1210	2015	Added a new section
	The state of the s		dedicated to plastic
			ground source heat
4101:2-13-01			pump loop systems
4101:2-13-01	1303.3.2	2015	Recognizes press-
			connect joints
	1306.4	2012	Added a standard for
	39 1700	Wind a Windows	liquid-level indicating
	10071		gages
	1307.1	2012	Added a standard for
/101.0 15.01			fuel oil valves
4101:2-15-01	1501.3	BBS initiated	Updated many
		changes	referenced standards

Hanshaw, Regina

From: Ohler, Debbie

Sent: Monday, October 24, 2016 4:07 PM

To: Sharier, John; 'Michael_Miller@CINFIN.com'

Subject: RE: BBS CODE UPDATES

Dear Mr. Miller and Mr. Sharier.

Thank you for taking the time to review the BBS draft Ohio Mechanical Code rule package. Your comments are appreciated and will be presented to the Code Committee for review. The next draft of our OMC rules will be sent out for E-notification and will incorporate fixes to the typographical errors that you have identified. Thank you, again. Regards, Debbie



Deborah D. Ohler, P.E., Staff Engineer Ohio Board of Building Standards PO Box 4009, 6606 Tussing Rd Reynoldsburg, OH 43068-9009 Office Phone: 614-644-2613 Fax:614-222-2147 dohler@com.state.oh.us http://www.com.ohio.gov/dico/BBS/

This message and any response to a may constitute a public record and thus may be publicly available to anyone who requests it.

From: Sharier, John

Sent: Monday, October 24, 2016 3:36 PM

To: Ohler, Debbie <debbie.ohler@com.state.oh.us>

Subject: FW: BBS CODE UPDATES

Hi Debbie,

I got this email and have to agree with Mr. Miller. The definition should have (steam is generated) in front of steam is superheated in the first sentence. The to, between pressure and vacuum should be or. I also found that in the second to last sentence, (not) should be in front of exceeding 250 degrees, so it would read: or


temperatures NOT exceeding 250 degrees F.

John



John Sharier
Boiler Chief
Ohio Department of Commerce
Division of Industrial Compliance
6606 Tussing Rd. Reynoldsburg, OH 43068
614.644.2541
www.com.ohio.gov

This message and any response to it may constitute a public record and thus may be publicly available to anyone who requests it.



From: Miller, Michael [mailto:Michael Miller@CINFIN.com]

Sent: Friday, October 07, 2016 5:08 PM

To: Sharier, John < john.sharier@com.state.oh.us>

Subject: BBS CODE UPDATES

http://www.com.state.oh.us/documents/bbs_CombinedOMCstakeholdermtg.pdf

I read through the proposed changes to the Mechanical Code and noted the following:

- Not all boilers generate superheated steam.
- · I think the to should be or.

Have a great weekend.

BOILER. A closed vessel in which water is heated, steam is superheated, or any combination thereof, under pressure to vacuum for use externally to itself by the direct application of heat from the combustion of fuels, or from electricity or nuclear energy. The term boiler includes fired units for heating or vaporizing liquids other than water where these units are separate from processing systems and are complete within themselves. Low-pressure boilers operate at pressures less than or equal to 15 pounds per square inch (psi) (103 kPa) for steam and 160 psi (1103 kPa) or temperatures exceeding 250 °F for water. High-pressure boilers operate at pressures exceeding those pressures and temperatures.

Michael Miller

Senior Machinery & Equipment Specialist

Office: 740-323-1070 Mobile: 740-644-1406 Facsimile: 877-356-7041

Confidentiality Notice: The information included in this e-mail, including any attachments, is for the sole use of the intended recipient and may contain information that is confidential and protected. Any unauthorized review, use, disclosure, distribution or similar action is prohibited. If you are not the intended recipient, please contact the sender and delete all copies of the original message immediately.

The information transmitted is intended solely for the individual or entity to which it is addressed and may contain confidential and/or privileged material. Any review, retransmission, dissemination or other use of or taking action in reliance upon this information by persons or entities other than the intended recipient is prohibited. If you have received this email in error please contact the sender and delete the material from any

*

computer.